



RECTANGULAR
2X10W COB
LED CEILING LIGHT
 180°rotatable



Size : mm



C10952


NETWEIGHT 0.9KG	CUTTINGSIZE 95X200MM	PACKING 1PC 23X15X12.5CM	PACKING 6PC 46X26X26.5CM
---------------------------	--------------------------------	---------------------------------------	---------------------------------------

Features:

High color rendering, uniform luminance, no light spot, no dark space. It was different from the lighting effects of general LED DOWNLIGHT in the market, substitute to the traditional lamp completely, and no maladjustment

Application:

Products are widely used as indoor main illumination lighting in the office, commercial center, shopping mall, supermarket, factory, etc.




Lamp Parameters :	Standard	Super-bright
Input Voltage	AC100-277V or AC200V-240V	
Frequency Range	50Hz~60Hz	
Led Consumption	20W	
System Consumption	23W	
Led Initial Flux	1800-2200LM	2300-2700LM
Color Rendering Index	>80	
Working Temperature	-40℃ ~ +55℃	
Fireproof Class	V0	
Power cable	2x0.75mm2	
Color of housing	black, white, silver	
Certificate	CE ROHS ERP V0 FCC	
Optical data:	IES	


Driver Parameters :

Brand	Lifud
Input	AC100-277V or AC200V-240V
Output	DC18-30V 350mA
Power Factor	0.9~0.97
Power Efficiency	87%
Certificate	UL, FCC, CE, SAA, PSE, CQC, TUV UL Certificate Number: E338140 SAA Certificate Number: TUV16071EA
Dimmable	Triac / dali / 1-10V / WIFI
MEANWELL: PLD-16-350 is optional	


Model No.	Beam angle	CRI	CCT	Illumination	Illumination (S)	Input Voltage(V)
C10952	30°/50°	>80	3000K	1800LM	2300LM	AC100-277V AC200-240V
			4000K	1900LM	2500LM	
			6000K	2200LM	2700LM	




Graphical Representation for
D1095 WW 50° (S)



Graphical Representation for
D1095 NW 50°



Graphical Representation for
D1095 NW 30° (S)



Graphical Representation for
D1095 WW 30°